

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3218)

Set post, cor. secs. 17, 18, 19 and 20, from which
A Fir 12" dia., bears N.1°W., 33 lks. dist.
A Fir 24" dia., bears N.1°E., 36 lks. dist.
A Fir 8" dia., bears S.3°W., 27 lks. dist.
A Fir 8" dia., bears S.75°E., 46 lks. dist.

Fd. and used in GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3259-60)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1, 1960 - C.S. 49/41-32

Found - Orig. 24" now 44" Fir snag, N.1°E., 23.8 ft. I open and find good scribing "T24S R7W S17"
No trace of other BTs found.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
S 18 | S 17
S 19 | S 20
1960

New BTs- 10" W.Fir bears S.78½°E., 22.7 ft. scribed S20 T24S R7W CS BT.
14" R.Fir bears N.44°E., 68.8 ft. scribed S17 T24S R7W CS BT.
9" W.Fir bears N.5°W., 64.3 ft. scribed S18 T24S R7W CS BT.
10" W.Fir bears S.60½°W., 64.9 ft. scribed S19 T24S R7W CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #889, surveyed Oct. 1975/April 1976 - (DCSO records Vol. 40 Page(s) 16005-06)

The Sec. Cor., perpetuated and recorded by Byron in 1960, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1960, from which the remains of the original bearing trees:

A Fir snag 44" dia., bears N.1°E., 39½ lks. dist., with scribe marks T24S R7W S17 visible on open blaze. (Rec. 36 lks.)

A root hole bears S.75°E., 46 lks. dist. with a down Fir alongside 18" dia., no marks visible.

and the remains of bearing trees mkd. by Byron:
(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 15" dia., bears N.44°E., 105 lks. dist., with scribe marks 4S R7W S17 CS visible on bark blaze.
A Grand Fir stump 15" dia., bears S.78½°E., 34½ lks. dist., with healed blaze.
A Grand Fir 13" dia., bears S.60½°W., 98½ lks. dist., with healed blaze.
A Grand Fir 14" dia., bears N.5°W., 100 lks. dist., with healed blaze.
and a new bearing tree:
A Fir 5" dia., bears S.13 3/4°E., 43½ lks. dist., mkd. T24S R7W S20 BT.

Mark Smalley - For: Roseburg Forest Products - 9/23/1996 - C.S. File 65/20-43

Found - 1960 DCS0 IPBC, good condition.
23" W.Fir, N.5°W., 64.3', good - healed.
44" Fir, N.1°E., 23.8', rotted.
14" Fir, N.44°E., 68.8', snag.
10" Fir, S.78½°E., 22.7', down - rotted.
22" Fir, S.60½°W., 64.9', good - healed.

New BTs- 13" Fir, N.28°E., 32.3', scribed "S17 BT"
8" Fir, S.86°E., 34.0', scribed "S17 BT"

Mark Smalley - For: Roseburg Forest Products - 10/14/2003 - C.S. File 65/48-41

Found - 1960 DCS0 IPBC, 2' tall loose in ground.
15" Fir N.28°E., 32.3 healed.
23" W.Fir snag N.5°W., 64.3 healed.
8" Fir S.86°E., 34.0 down - healed.

New - 12" Fir N.86°E., 29.6' scribed "S17 BT"
18" W.Fir N.34°E., 26.6' scribed "S17 BT"
Dec. 19°

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCS0 records Vol. 57 Page(s) 22367-8)

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 1¼" dia., firmly set, projecting 20" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A fir snag, 44" dia., bears N.1°E., 24.7 ft., with fragmentary scribe marks visible on an opened blaze.
(Record, 26.1 ft.)
continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole bears S.75°E., 30.4 ft., with no remains of the trunk visible.
and remains of BTs mkd. by the Douglas County Surveyors Office in 1960, reported by Jelley
A fir snag, 21" dia., bears N.44°E., 69.3 ft., with a healed double blaze.
A fallen fir snag, 22" dia., bears S.56¾°W., 65.0 ft., with a healed blaze. (Record S.60½°W.)
A fir snag, 25" dia., bears N.5°W., 64.0 ft., with a healed blaze. (Record, 66.0 ft.)
and BTs mkd. by Smalley, Oregon in 1996 and 2003
A fir, 16" dia., bears N.27½°E., 32.5 ft., with a healed blaze.
A fir, 20" dia., bears N.32½°E., 26.9 ft., with scribe marks S17 BT visible on a partially healed blaze.
A fir, 13" dia., bears N.82½°E., 29.7 ft., with fragmentary scribe marks visible on a partially healed blaze.
and new accessories
An iron rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.18°06'46" E., 8.7 ft. with aluminum cap mkd. T24S R7W RM S20 8.7 FT TO COR 2005 and an arrow pointing to the cor.
An iron rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.49°27'50"W., 7.5 ft. with aluminum cap mkd. T24S R7W RM S19 7.5 FT TO COR 2005 and an arrow pointing to the cor.
The geographic position (NAD 83 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.
The corner of sections 17, 18, 19 and 20:
Latitude: 43°28'35.25"N Longitude: 123°33'54.25"W