

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3219)

- 
- Set post, cor. secs. 7, 8, 17 and 18, from which
- A Fir 15" dia., bears S.87°E., 25 lks. dist.
  - A Fir 12" dia., bears N.20°E., 12 lks. dist.
  - A Fir 24" dia., bears N.16°W., 28 lks. dist.
  - A Fir 24" dia., bears S.45°W., 21 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3260-61)

-----

At a point, 1.22 chs. W. of old cor. to secs. 7, 8, 17 and 18, old cor. post gone, bearing trees mkd. as per notes furnished by surveyor general, where I set a post 4 ft. long, 4" sq.m, 24" in the ground for cor. marked T24S S8 on NE.; R7W S17 on SE.; S18 on SW.; and S7 on NW. faces with 5 notches on E. and 4 notches on S. edges, from which

- A W.Fir 10" dia., bears N.40°E., 43 lks. dist. mkd. T24S R7W S8 BT.
- A W.Fir 20" dia., bears S.8°E., 10 lks. dist. mkd. T24S R7W S17 BT.
- A W.Fir 14" dia., bears S.75°W., 20 lks. dist. mkd. T24S R7W S18 BT.
- A Y.Fir 14" dia., bears N.15°W., 9 lks. dist. mkd. T24S R7W S7 BT.

I destroyed all trace of this old cor. which is described in old notes as being a post with bearing trees.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Dec. 3, 1957 - C.S. File 49/41-4

-----

Found - Orig. 10" now 18" W.Fir snag N.40°E., 28.4 ft. Has open face, good scribing.  
The SE. and SW. orig. BTs would be in log road. I can find no trace of orig. NW. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	7	W
S	7	S	8		
S	18	S	17		
				1957	

Corner falls on cut slope at North side of log road.  
New BTs- 13" W.Fir bears S.49½°E., 48.3 ft. scribed S17 T24S R7W CS BT.  
48" R.Fir bears N.62½°W., 27.0 ft. bark scribed S7 T24S R7W CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

16" W.Fir bears N.41°E., 58.1 ft. scribed S8 T24S  
R7W CS BT.  
6" W.Fir bears S.59½°W., 119.7 ft. scribed S18 T24S  
R7W CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #889, surveyed Oct. 1975/April 1976 - (DCSO records Vol. 40 Page(s) 16008)

-----

The Sec. Cor., perpetuated and recorded by Byron in 1957, from original evidence no longer in existence, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1957, from which the remains of bearing trees mkd. by Byron:

- A Fir snag 16" dia., bears N.41 3/4°E., 88½ lks. dist., with scribe marks 24S R7W CS BT visible on open blaze.
- A Grand Fir 20" dia., bears S.50°E., 73 lks. dist., with healed blaze.
- A root crown, bears S.60¼°W., 180 lks. dist., with a down Fir alongside 8" dia., with scribe marks T24S R7W S18 CS BT visible on open blaze.
- A Fir snag, 48" dia., bears N.63°W., 41 lks. dist., with scribe marks T24S R7WS7 CS visible on bark blaze.

and new bearing trees;

- A Fir 5" dia., bears N.45½°E., 11½ lks. dist. mkd. T24S R7W S8 BT.
- A Grand Fir 8" dia., bears S.59¼°W., 201 lks. dist. mkd. T24S R7W S18 BT.
- A Fir 6" dia., bears N.84 3/4°W., 27 lks. dist. mkd. T24S R7W S7 BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22371)

-----

The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 1¾" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by the Douglas County Surveyors Office in 1957, reported by Jelley

- A tin-capped, sawed fir stump, 25" dia., bears S.50°E., 48.2 ft with no scribe marks visible on an opened blaze
- A decayed fir snag, 50" dia., bears N.63°W., 27.1 ft., with scribe marks S R visible in the bark.

and remains of bearing trees mkd. by Jelley

- A fir, 15" dia., bears N.45½°E., 7.6 ft., with a healed blaze.

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A dead fir, 14" dia., bears S.59¼°W., 132.7 ft., with a  
healed blaze.  
A fir, 22" dia., bears N.84¾°W., 17.8 ft., with a healed  
blaze.  
and new bearing tree  
A fir, 12" dia. bears N.15°W., 13.0 ft mkd. T24S R7W S7 BT