

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 202700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A W.Oak 38" dia., bears S.10°W., 54 lks. dist., with a healed blaze.
A Fir 55" dia., bears N.13°W., 160 lks. dist., with a healed blaze.
and the remains of the bearing trees mkd. by Byron:
A Fir 17" dia., bears N.14°E., 20 lks. dist., with a healed blaze.
A Fir snag 12" dia., bears N.57½°W., 58 lks. dist., with a healed blaze.
and a new bearing tree:
A Fir 19" dia., bears N.26°W., 62½ lks. dist. mkd. T23S R7W S31 BT.

Fd. OK, April 1992 by Dolan - M 115-3

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - Sept. 18, 2014 - C.S. File 67/42-1

Found - A 2½" dia., brass cap (properly marked) on a 1" I.D. iron pipe leaning NW'ly 0.5 ft. and protruding 18" above ground. 1960
All accessories are measured from plumb position of fd BC monument.
OBTs - A W.Oak 16" dia., now 39" dia., W.Oak with healed scar of 1960 scribing search; bears S.11½°E., 35.6 ft. (rec. S.10°W., 35.6 ft.)
A fir 24" dia., now a 56" dia., 3½ ft. tall sawed and rotted fir stump (which is opened but no scribing is fd); bears N.10°W., 107.5 ft. (rec. N.13°W., 105.6 ft.)
A fir 8" dia., now a 48" dia., 4 ft. tall partially rotted sawed D.fir stump which is opened to find the scribing "R7W T24S S5; bears S.39¼°E., 137.3 ft. (rec. S.40°E., 137.3 ft.)
1960 BTs- A 14" R.Fir, now a 30" dia., D.Fir with a fully healed double blaze; bears N.14°E., 13.0 ft. (as per rec.)
A 10" W.Fir, now a 12" dia., 5" tall mostly rotted away fir stump; bears N.57½°W., 37.8 ft. (as per rec.)
1983 BT- A fir 19" dia., now a 19" dia., 3 ft. tall fir stump which was sawed but now is mostly broken off to ground level and still has the intact but loose face with all the correct scribing. This stump bears N.26°W., 41.3 ft. (as per rec.)
New - The fd BC monuments plumb position is referenced out, the monument is removed and is reset plumb and now protruding 6" above ground. cont.

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 202700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 20" dia. D.Fir scribed "T23S R7W S32 CS" "BT" on a double blaze; bears N.67°E., 24.7 ft.
An 11" dia. G.Fir scribed "T23S R7W S31" "CSBT" on a double blaze; bears N.32½°W., 26.5 ft.
Note - A very old 16" dia., 6 ft. tall yew post bears approx. N.45°W., 1.3 ft. A fence corner with fences running north and West bears N.35°W. 3 ft. Corner is on gentle westerly slope in very old second growth forest of mixed fir, some oak. Compass decl. 15½°E.