

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3218)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.88°W., 30 lks. dist.
A Myrtle 6" dia., bears N.80°E., 12 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 30, 1958 - C.S. File 49/41-16

Found - Orig. 12" now 35" Fir snag, S.88°W., 19.8 ft. I fall snag and find good scribing "BT".
A clump of Myrtle checks brg. & dist. for orig. NE.
BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
¼ $\frac{S\ 17}{S\ 20}$
1958

New BTs- 7" W.Oak bears N.3°E., 11.1 ft. scribed ¼ S17 CS BT.
14" R.Fir bears S.33°W., 21.1 ft. scribed ¼ S20 CSBT

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #889, surveyed Oct. 1975/April 1976 - (DCSO records Vol. 40 Page(s) 16004-05)

The ¼ sec. cor., perpetuated and recorded by Byron in 1958, monumented with an iron post 1½" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1958, from which the remains of the original bearing trees:

A sawed Fir stump 35" dia., bears S.86°W., 31½ lks. dist. with scribe marks BT visible on open blaze. (Rec. S.88°W., 30 lks.)
and the remains of bearing trees mkd. by Byron:
A W.Oak 10" dia., bears S.½°W., 17 lks. with healed blaze.
A Fir snag 15" dia., bears S.31°W., 32 lks. dist. with scribe marks ¼ S20 CS BT visible on open blaze.
and a new bearing tree:
A W.Oak 10" dia., bears S.3½°E., 58 lks. mkd. ¼ S20 BT.

Mark Smalley - For: Roseburg Forest Products - 9/23/1996 - C.S. File 65/20-

Found - 1958 DCSO IPBC
W.Oak, 11" S.½°W., 17 lks.
New BTs- Oak, 9" N.38°E., 22.0', scribed "¼ S17 BT"
Oak, 10" N.54°E., 46.5', scribed "¼ S17 BT"
No other trees reasonably accessible. _____