

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 243700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCS0 records Vol. 6 Page(s) 2462)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.50°W., 79 lks. dist.
A Fir 30" dia., bears North, 18 lks. dist.

Survey by R.C. Grant - Wit: G.E. Johnson; E.J. Madison - Oct. 13, 1952 - C.S. File 41/103

Set ¾" I.Pipe 3 ft. long, set from stump of original BT (Fir with scribes visible), S.45°W., 50 lks.
Marked new BT:
A 9" Oak N.8°W., 136.2 ft.
There was no other trees available.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - Sept. 1960 - C.S. File 49/49-8

Found ¾" I.P. at corner and BT recorded by Grant. Also find base of large rotted Fir stump that checks orig. dist. and brg. for SW BT.
Corner pipe is alongside 8" Yewood fence post and is scribed "¼ S32".
New BT - 10" W.Oak bears S.34°W., 29.0 ft. scribed "¼ S32 CS BT".

BLM Resurvey by C. Albert White, Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #515, Surveyed June/Oct. 1963 - (DCS0 records Vol. 32 Page(s) 13476)

The ¼ sec. cor. of sec. 32 only, perpetuated and recorded by Grant in 1952, monumented with an iron pipe, ¾" dia., firmly set, protruding 6" above the ground, from which the remains of the only remaining bearing tree:
A charred and rotted Fir stump 36" dia., bears S.50°W., 81 lks. dist., 79 lks. dist. to face, with no marks remaining. (Rec. 79 lks.)
and bearing tree by Grant:
An Oak 10" dia., bears N.8°W., 206 lks. dist., with a healed blaze.
and bearing tree by Byron in 1960:
A W.Oak 10" dia., bears S.34°W., 44 lks. dist. mkd. ¼ S32 CS BT.
At the corner point
(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 243700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,
with brass cap mkd:

T 23 S R 7 W
¼ S 32
1963

Deposit 3/4" iron pipe alongside iron post.

Fd. OK, March 1983 by D. Bentz - M 90-38 A&B
Fd. BC & 2 BTs, May 2006 by C. Sweeden - M151-20
Fd. Ok by DCS0 9/26/2006, C.S. 67/14-38: All fd as per rec