

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION CC for Secs. 32 & 33 only, (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. R. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3259)

-----  
Intersect south Bdy. of the Tps. (T24-7) 79 lks. E of cor. to secs. 4, 5, 32 and 33; at which point I set a post, 4 ft. long, 4" sq., 24" in the ground for closing corner to secs. 32 and 33, mkd. C C T24S R7W on N.; S33 on E.; and S32 on W.; with 4 notches on E and 2 notches on W. faces, from which  
A Fir 15" dia., bears N.86°E., 19 lks. dist., mkd. T24S R7W S33 BT.  
A Fir 11" dia., bears N.35½°W., 25 lks. dist., mkd. T24S R7W CC S32 and 33 BT.

Doug. County Surveyors Office - Milo Godfrey, Deputy - Vernon Tracy - June 18, 1962 - C.S. File 49/41-50

-----  
Found - Double W.Fir now 42" N.35½°W., 16.5 ft. This tree has been previously chopped open, scribing visible on old face "24 SR CC".  
D.Fir now 24" N.86°E., 12.5 ft. shows good scar. Did not cut open.  
Set Brass cap at cor. mkd: County Surveyor's T24S R7W S32|S33 Office, 1962 C.C.  
Rescribe -24" D.Fir N.86°E. 12.5 ft. mkd "T24S R7W CC S33 CSBT  
New BT - 7" W.Fir N.64°W., 33.9 ft. mkd. T24S R7W CC S32 CS BT.

BLM resurvey by Jelley and Rogers, 1979, found brass cap and three BTs. (DCSO records, Volume 43 Pages 16653-54)

Found Ok by Douglas Co. Surveyors Office - Randall W. Smith & Stephen J. Flause - 2/18/1998 - C.S. File 64/79-9

BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20297-8)

-----  
The closing cor. of secs. 32 & 33, T. 24 S., R. 7 W., 0.785 chs., monumented with an iron post, 1½" diam., firmly set, projecting 8" above ground, with brass cap mkd.  
COUNTY SURVEYORS OFFICE  
T 24 S  
S 32 | S 33  
CC  
R 7 W  
1962

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION CC for Secs. 32 & 33 only (south)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees  
A sawed fir stump, 30" diam., bears N.86°E., 19 lks., with  
healed blaze.  
A sawed fir stump, 49" diam., bears N.35½°W., 25 lks.,  
with healed blaze.  
and the remains of a bearing tree mkd. by Godfrey, in 1962  
A sawed fir stump, 48" diam., bears N.65½°W., 51 lks.,  
with healed blaze.  
and new bearing trees  
A fir, 9" diam., bears N.80°E., 41 lks., mkd. T24S R7W S33  
BT.  
A fir, 7" diam., bears N.17½°W., 11 lks., mkd. T24S R7W  
S32 BT.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor  
and Robert H. Browning, Survey Tech, under Group No. 2300  
surveyed May 2006 - (DCS0 records BLM Plat 2011-2 & Vol. 57  
Page(s) 22690)

-----  
As per described by Siebold & Rogers in 1997  
Latitude 43°25'57.37"N. Longitude 123°32'42.45"W.  
(NAD 1983 (CORS))