

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3205)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.28°E., 45 lks. dist.
A Fir 10" dia., bears S.20°W., 67 lks. dist.

Fd. and used in GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3259)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon "Ray" Tracy, crew - June 18, 1962- C.S. File 49/41-49

Found - Fir, now 36" S.25°E., 29.7 ft., uprooted and down, had been opened previously, good scribing "S" visible on old face. This tree had been rescribed "¼SBT" shortly before it fell.

No trace of other original BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
¼ S 32 | S 33
1962

New BTs- 11" D.Fir N.23°E., 42.3 ft. mkd. ¼ S33 CS BT.
10" W.Fir S.38°W., 31.8 ft. mkd. ¼ S32 CS BT.
A scribed stake mkd. "¼ S" bears S.47½°E., 17.5 ft.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979 - (DCSO records Vol. 43 Page(s) 16652-53)