

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300161

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 33

Alias <u>868210</u>	Description <u>M.C. on left bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3205)

-----  
Marked an Ash 10" dia., for meander post, left bank of Umpqua River, from which  
An Oak 18" dia., bears N.2°W., 334 lks. dist.  
An Ash 10" dia., bears N.80°E., 6 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1, 1960 - C.S. File 49/41-34

-----  
Found - Orig. 18" now 24" W.Oak snag, N.2°W., 220.4 ft. We open and find good scribing "S32".  
Other orig. BT not found.  
Meander corner in river bed. I set Witness Corner 220 ft. North of corner. Set brass cap at wit. cor. marked:  
County Surveyors Office  
T 24 S R 7 W  
Wit. Cor. S32|S33  
1960  
New BTs- 16" W.Oak bears N.76°E., 27.6 ft. scribed W.C. MC S33 CS BT.  
14" R.Fir bears S.72½°W., 33.0 ft. scribed W.C. MC S32 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979 - (DCSO records Vol. 43 Page(s) 16651)

-----  
The original meander cor. of secs. 32 and 33, on the left bank of the Umpqua River, determined from the remains of an original bearing tree:  
A root hole bears N.2°W., 334 lks. dist., with a down Oak alongside, 22" dia., with scribe marks S32 visible on open blaze.  
At the corner point  
Set an brass tablet, 3 1/2" stem, in drill hole in bedrock with top marked:  
T 24 S | R 7 W  
S 32 | S 33  
M C  
1979  
from which new bearing trees  
A triple Cedar 23" dia., bears N.3½°E., 266 lks. dist., mkd. T24S R7W S33 MC BT.  
A Cedar 25" dia., bears N.15°W., 271 lks. dist. mkd. T24S R7W S32 MC BT.  
(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300161

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 33

Alias 868210 Description M.C. on left bank of Umpqua River

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

From this point, a cor. established by Byron in 1960, bears North, 3.33 chs. dist., monumented with an iron post, 1½" dia., firmly set, projecting 16" above ground, with brass cap mkd. in 1960, from which bearing trees mkd. by Byron

An Oak 18" dia., bears N.76°E., 42 lks. dist., with healed blaze.

A Fir 18" dia., bears S.71½°W., 50 lks. dist., with healed blaze.