

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3205)

Set post cor. secs. 28, 29, 32 and 33, from which
 An Oak 24" dia., bears N.3°E., 255 lks. dist.
 An Oak 10" dia., bears N.3°W., 285 lks. dist.
 An Oak 15" dia., bears S.87½°E., 338 lks. dist.
 No tree convenient SW. (sec. 32)

H.L. Eppstein, Surveyor - Wit: Ernie Short; Rudolph Ritzman; J.C. Clayton - March/April 1926 - C.S. File 14/36 and Vol. 4 Page 3

Found old BT in sec. 28 and set corner from it. Then checked out and found BTs in secs. 29 and 33 in evidence. Set a 2" x 2" x 20" square iron pipe for corner, also 4" x 4" x 4' Oak stake. Marked new BTs:
 15" W.Oak N.81°W., 35 lks.
 15" W.Oak N.62°E., 83 lks.
 15" W.Oak S.67°30'E., 98 lks.
 No trees near in sec. 32.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1, 1960 - C.S. File 49/41

Found all tree BTs as recorded by Eppstein in 1928, except we find NE. BT should be N.59°E. (Rec. N.62°E). BTs show good scars. I do not open.
 Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	7	W
	S	29		S	28
	S	32		S	33
				1960	

BTs all in good condition. No new BTs scribed.
 Pipe set by Eppstein at corner, not found.

Bruce Shaner - For: U.S. Bureau of Land Management - Dec. 11, 1972 - M 49-7

Found - DCSO brass cap.
 18" W.Oak, face visible, bears N.81°W., 23.1 ft.
 20" W.Oak, face visible, bears S.67½°E., 64.7 ft.
 22" W.Oak bears N.59°E., 54.0 ft. (Rec. 54.8 ft.)
 Orig. 32" Oak, face visible but rotted out, bears N.3°E.,, 168.3 ft.
 New BT - 12" D.Fir scribed "T24S R7W S32 BT", bears S.61 3/4°W., 16.6 ft. (Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. and used in BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15298)

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979 - (DCSO records Vol. 43 Page(s) 16650-51)

Survey by Mark Smalley - For: Scott Timber Co. - Sept. 1996 -M 124-27

Found - DCSO 1960 brass cap.
18" Oak N.81°W., 23.1 ft., snag. (1926)
22" Oak N.59°E., 54.0 ft., snag. (1926)
20" Oak S.67½°E., 64.7 ft., snag. (1926)
18" Fir S.61 3/4°W., 16.6 ft., snag (1972)
New BTs- 12" Fir N.75°W., 16.3 ft. scribed "S 29 BT"
17" Fir N.41°E., 56.4 ft. scribed "S 29 BT"
15" Fir S.56°E., 45.7 ft. scribed "S 29 BT"

Fd. Ok by Neil Hibbs - 5/2004 - M145-34
Fd. per rec. 10/2023 - B Heichel M183-1