

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3209)

Set post, cor. secs. 20, 21, 28 and 29, from which
An Oak 10" dia., bears N.35°W., 58 lks. dist.
A Laurel 24" dia., bears S.42°W., 54 lks. dist.
A Fir 18" dia., bears S.40°E., 15 lks. dist.
A Fir 30" dia., bears N.22°E., 26 lks. dist.

H.L. Eppstein, County Surveyor - Wit: Rudolph Ritzman; J.C. Clayton; Ernie Short - April 1926 - C.S. File 14/36 and Vol. 4 Page 3

Found old Laurel BT, also Firs NE. and SE. (SE Fir rotten but found scribe.)
Set 1/2" buggy axle for corner, also 4" x 4" x 4 ft. post and marked new BTs as follows:
Fir 48", S.54°E., 27 lks.
Fir 12", S.60°W., 54 lks.
Fir 12", N.62°W., 57 lks.
NE. old tree good.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1, 1960 - C.S. 49/41-31

Found - Buggy axle, loose and at South side of old logging road. True corner is about center of log road. Orig. 30" now 44" Fir, N.22°E., 17.2 ft., shows faint scar.
Frear's SW. and SE. BTs show good scars. The NW. BT down.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
S 20 | S21
S 29 | S28
1960

New BT - 40" R.Fir bears N.39°W., 101.0 ft. bark scribed "S20 T24S R7W CS BT"

Fd. OK Feb. 1982 by G. Grubb - M 91-27

Survey by Mark Smalley - For: Scott Timber Co. - Sept. 1996 -M 124-27

Found - DCSO 1960 brass cap and iron pipe.
44" Fir N.22°E., 17.2 ft., down. (Orig.)
48" Fir S.51°E., 30.2 ft., healed (1960)
(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

24" Fir S.60°W., 35.6 ft., healed (1960)
New BTs- 8" Fir N.81°W., 19.7 ft. scribed S 20 BT.
8" Fir N.79°E., 41.2 ft. scribed S 21 BT.