

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3211)

Set ¼ sec. post, from which
 An Oak 10" dia., bears S.80°W., 40 lks. dist.
 An Oak 10" dia., bears S.63°E., 137 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - March 1960 - C.S. File 49/41-26

Found - Orig. 10" now 24" W.Oak S.63°E., 90.4 ft.,
 previously opened, shows good scribing "¼S"
 No trace of orig. SW. BT found.

Set Brass cap at cor. mkd: County Surveyors Office
 T 24 S R 7 W
 ¼ S20 | S21
 1060

New BTs- 12" W.Oak bears N.43°E., 26.2 ft. scribed ¼ S21 CSBT
 12" W.Oak bears N.84°E., 54.8 ft. scribed ¼ S21 CSBT
 No trees near West of line.

Fd. OK Jan. 12, 1982 by G. Quibell, DCSO - C.S. File 61/30-10

Survey by Mark Smalley - For: Scott Timber Co. - Sept. 1996
-M 124-27

Found - DCSO 1960 brass cap and iron pipe.
 15" Oak N.43°E., 26.2 ft., healed. (1960)
 20" Oak N.85°E., 54.8 ft., healed. (1960)
 24" Oak S.63°E., 90.4 ft., healed. (Orig. BT)
New BT - 10" Fir N.61°W., 18.0 ft. scribed ¼ S BT.

Found OK by B. Rogers, June 1998 - Partition plat 1998-0084.