TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3212)

Set ¼ sec. post, from which
An Oak 12" dia., bears N.1°W., 175 lks. dist.
An Oak 12" dia., bears N.8°E., 188 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #889, surveyed Oct. 1975/April 1976 - (DCSO records Vol. 40 Page(s) 16002-03)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 17 S 16
T 24 S R 7 W
1976
from which
A Fir 12" dia., bears S.26 3/4°E., 32½ lks. dist. mkd. ¼ S16 BT.
A Fir 6" dia., bears S.22¼°W., 20½ lks. dist. mkd. ¼ S17 BT.

Mark Smalley - For: Roseburg Forest Products - April 1998 - M 128-74

Found - 1976 Cadastral brass cap on iron pipe.
15" Fir, S.26¾°E., 20.5', healed.
6" Fir, S.22¼°W., 13.5', healed.
Scribed- 26" Fir, S.77°E., 20.1', "¼ S BT"
22" Fir, S.2°W., 6.4', "¼ S BT"