

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3212)

-----  
Set post, cor. secs. 8, 9, 16 and 17, from which  
An Oak 12" dia., bears S.3°W., 310 lks. dist.  
An Oak 12" dia., bears S.4°E., 387 lks. dist.  
An Oak 12" dia., bears N.6°W., 126 lks. dist.  
No tree convenient NE.

Cor. fd. and used in GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3269)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Dec. 3, 1957 - C.S. File 49/41-5

-----  
Found - Orig. 12" now 24" Oak. This BT is down. Sections have been cut and I find chips with reverse scribing "S1", S3°W., 204.6 ft.  
I can find no trace of the Orig. SE. & NW. BTs.  
Fence corner bears East, 3.0 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 7 W  
S 8 | S 9  
S 17 | S 16  
1957

New BTs- 13" R.Fir bears S.16½°W., 22.8 ft. scribed S17 T24S  
R7W CS BT.  
14" R.Fir bears S.76°E., 8.4 ft. scribed S16 T24S  
R7W CS BT.  
14" W.Oak bears N.53½°E., 23.0 ft. scribed S9 T24S  
R7W CS BT.  
10" R.Fir bears N.26°W., 36.2 ft. scribed S8 T24S  
R7W CS BT.

Fd. & used on BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #889, surveyed Oct. 1975/April 1976 - (DCSO records Vol. 40 Page(s) 16003)

Mark Smalley - For: Rsbfg Forest Products - 4/1998 - M 128-73

-----  
Found - 1957 County brass cap on iron pipe.  
26" Fir, S.76°E., 8.4', healed.  
28" Fir, N.5°E., 45.6', scribe visible.  
24" Fir, S.16½°W., 22.8', down.  
14" W.Oak, N.53½°E., 23.0', down rotten.  
18" Fir, N.26°W., 36.2', down.  
Scribed- 12" Fir, N.41°E., 29.4', "S 9 BT".

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias	Description

Ken Hoffine - For: Lone Rock Timber Co. - 7/2001 - M 138-42  
-----  
Found - 1957 Douglas Co. brass cap.  
25" D.Fir bears S.79°E., 8.2 ft. (rec. S.76°E., 8.4 ft.) well healed face & BLM tag.  
New - 27" D.Fir bears N.5¾°E., 44.3 ft. We scribe T24S R7W S9 BT and tag tree.  
Note - Corner lies in East West fence line & is east 12 ft. from tree used as fence corner.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55 Page(s) 21303-4)  
-----  
The cor. of secs. 8, 9, 16, & 17, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd from which the remains of BTs mkd. by the DCSO in 1957, reported by Jelley  
A roothole bears N.64¼°E., 20.9 ft., with fallen oak trunk, size indeterminate, lying alongside, no marks visible. (Record, N.52¾°E., 24.4 ft.)  
A fir, 26" dia. bears S.80°E., 8.2 ft. with a healed blaze  
A roothole bears S.12¾°W., 25.4 ft., with fallen fir trunk, 23" dia., lying alongside, no marks visible. (Record, S.17¼°W., 23.1 ft.)  
A roothole bears N.28¼°W., 34.6 ft., with fallen fir trunk, 18" dia., lying alongside, no marks visible. (Record, N.25½°W., 36.3 ft.)  
and a BT mkd. by Smalley, in 1998  
A fir, 12" dia., bears N.36¼°E., 29.4 ft., with fragmentary scribe marks visible on partially healed blaze  
and a BT mkd. by Hoffine  
A fir, 27" dia., bears N.5¾°E., 44.3 ft., with fragmentary scribe marks visible on a partially healed blaze.  
and a new bearing tree  
A fir, 18" dia., bears N.85½°W., 71.7 ft., mkd. T24S R7W S8 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

continued next page

2

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22372)

-----  
The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by the Douglas County Surveyors Office, reported by Skeesick

A roothole bears N.64¼°E., 20.9 ft., with fallen trunk, size indeterminate, lying alongside, with no marks visible.

A fir, 29" dia., bears S.80°E., 8.2 ft., with a healed blaze.

A roothole bears S.12¼°W., 25.4 ft., with fallen trunk, 23" dia., lying alongside, with no marks visible.

A roothole bears N.28¼°W., 34.6 ft., with fallen trunk, 18" dia., lying alongside, with no marks visible. and bearing tree mkd. by Smalley, reported by Skeesick

A fir, 13" dia., bears N.36¼° ., 29.4 ft., with fragmentary scribe marks visible on a partially healed blaze.

and bearing tree mkd. by Hoffine, reported by Skeesick

A fir, 30" dia., bears N.5¾°E., 44.3 ft., with fragmentary scribe marks visible on a partially healed blaze.

and bearing tree mkd. by Skeesick

A fir, 22" dia., bears N.85½°W., 71.7 ft., with no scribe marks visible on a mostly healed blaze.

The geographic position (NAD 83 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.

The corner of sections 8, 9, 16, and 17:

Latitude: 43°29'27.31"N      Longitude: 123°32'41.92"W