

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300520

PRIMARY CORNER DESCRIPTION South 1/16 cor betw Secs 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3213)

Set post, from which
A Fir 6" dia., bears N.7°E., 4 lks. dist.
A Fir 24" dia., bears S45°W., 29 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 7, 1960 - C.S. 49/41-41

Found - Orig. 24" now 28" Fir snag, S.45°W., 19.2 ft., previously opened, shows good scribing "BT".
Orig. NE. BT, not found.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
W.C. S 1/16 S8|S9
1960

New BTs- 12" R.Fir bears N.62½°W., 10.4 ft. scribed S1/16 S8 CS BT.
16" R.Fir bears S.72°E., 7.0 ft. scribed S1/16 S9 CS BT.

(Corner renewed by Byron as a "witness corner" but is not a witness cor. per L. Murphy, BLM, Portland - 8/4/77)

Cor. fd. & tied in BLM Resurvey by C. Albert White, Cadastral Surveyor & Donald R. Beck, Surveying Tech, Under Group #515, Surveyed June/Oct. 1963 - (DCSO records Vol. 32 Page 13481)

Douglas Co. Surveyors Office - Karen Reed; P.L. Earle, crew - April 16, 1979 - C.S. File 60/24-23

Found - 1" x 36" I.P. with 1960 brass cap mkd. in 1960.
An orig. 24" Fir now a 28" snag, bears S.45°W., 19.2 ft. to face, no visible scribing, snag burned and rotten.
A 12" R.Fir now 18", bears N.62½°W., 10.4 ft. with well healed double blaze.
A 16" R.Fir bears S.72°E., 7.0 ft. with well healed double blaze.

We x'ed out W.C. on cap and stamped 1979 on it in additon to the 1960. Cap at appropriate brg. & dist. from orig. BT.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55 Page(s) 21304-5)

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300520

PRIMARY CORNER DESCRIPTION South 1/16 cor betw Secs 8 & 9

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

The S 1/16 sec. cor. of secs. 8 & 9, monumented with an iron post, 1 1/4" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd from which the remains of an original bearing tree

- A decayed fir stump, size indeterminate, bears S.45°W., 20.5 ft. no marks visible.

and remains of BTs mkd. by the DCSO in 1960

- A fir, 22" dia., bears S.72°E., 7.0 ft., with a healed blaze. (Record, 6.6 ft.)
- A fir stump, 18" dia., bears N.62 1/2°W., 10.6 ft., with a healed blaze.

and new bearing tree

- A fir, 13" dia., bears S.0 1/4°E., 30.6 ft., mkd. X BT.

Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description