

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3213)

-----  
Set ¼ sec. post, from which  
A Fir 9" dia., bears S.60°W., 35 lks. dist.  
A Fir 24" dia., bears East, 30 lks. dist.

Cor. fd. and used in GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3269)

Douglas Co. Surveyors Office - Gary L. Langlitz; P. Earle, crew - May 23, 1974 - C.S. File 56/51-12

-----  
Found - 52" D.Fir with GL0 and Wilford N. Haines location posters attached. This tree has been previously opened. No marks visible. We open further and find good scribing "BT".

We find no evidence of orig. SW. BT.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 7 W  
S 8 | S 9  
1/4  
1974

at record bearing and distance from an orig. 24" now 52" D.Fir bearing East, 19.8 ft.

New BTs- A 12" Grand Fir bears N.86½°W., 16.6 ft. scribed ¼ S8 CS BT.

An 11" Red Cedar bears N.17°W., 27.9 ft. scribed ¼ S8 CS BT.

Original calls to creek crossings to the North of the ¼ cor. do not correspond with existing ground conditions. A small spring drainage, course N.50°W., bears North approx. 47 ft. (Rec. 16.5 ft.) A small stream, course West, bears North approx. 155 ft. (Rec. 290.4 ft.)

Found OK by D. Edwards, May 2000 - M134-70  
Found OK by K. Hoffine, July 2001 - M138-42

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55 Page(s) 21305)

-----  
The ¼ sec. cor. of secs. 8 & 9, perpetuated by DCSO, in 1974, monumented with an iron post, 1¼" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd from which the remains of an original bearing tree  
continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree  
A decayed fir stump, 50" dia., bears East, 19.8 ft., with  
fragmentary scribe marks visible on opened blaze.  
and remains of BTs mkd. by the DCSO  
A decayed fir stump, size indeterminate, bears N.88°W.,  
16.6 ft., no marks visible.  
A decayed cedar stump, 15" dia., bears N.17°W., 27.9 ft.  
no marks visible.  
and new bearing trees  
A fir, 9" dia., bears N.1°E., 17.4 ft., mkd. ¼ S9 BT.  
A fir, 5" dia., bears N.82¾°W., 18.3 ft., mkd. X BT  
A decayed fir stump, 50" dia., bears East, 19.8 ft., with  
fragmentary scribe marks visible on opened blaze.  
and remains of BTs mkd. by the DCSO  
A decayed fir stump, size indeterminate, bears N.88°W.,  
16.6 ft., no marks visible.  
A decayed cedar stump, 15" dia., bears N.17°W., 27.9 ft.  
no marks visible.  
and new bearing trees  
A fir, 9" dia., bears N.1°E., 17.4 ft., mkd. ¼ S9 BT.  
A fir, 5" dia., bears N.82¾°W., 18.3 ft., mkd. X BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center, unless otherwise  
described in the corner description