

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found OK by D. Edwards, May 2000 - M134-70

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55 Page(s) 21306-7)

The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2½" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd
from which the remains of BTs mkd. by White and Beck
 A decayed fir stump, 16" dia., bears N.44½°E., 100.5 ft.,
 with scribe marks S9 BT visible on a decayed blaze.
 (Record, 101.6 ft.)
 A decayed fir stump, size indeterminate, bears N.69¾°W.,
 133.3 ft., no marks visible.
and new bearing trees
 A fir, 22" dia., bears N.27¾°E., 126.8 ft., mkd. T24S R7W
 S4 BT.
 A black walnut, 32" dia., bears S.41¾°E., 120.9 ft., mkd.
 T24S R7W S9 BT.
 A fir, 19" dia., bears N.68¾°W., 199.8 ft., mkd. T24S R7W
 S5 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description