


PRIMARY CORNER DESCRIPTION Witness Special Meander Cor.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley and Wayne L. Rogers,  
 Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979  
 - (DCSO records Vol. 43 Page(s) 16658)

-----  
 From the center N 1/16 sec. cor of sec. 33  
 N.89°55'W., on the E & W center line of the NW¼ of sec. 33  
24.26 chains - Point selected for the witness special meander  
 cor. on the E. & W. center line of the NW¼ of sec. 33  
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
 brass cap marked:



from which  
 A Myrtle, 18" dia., bears N.59°E., 26½ lks., mkd: X BT.  
 A Fir, 18" dia., bears South, 9½ lks., mkd: X BT.  
25.45 chains - Right bank of Umpqua River, bears N.45°E., and  
 S.45°W., course N.45°E.; thence across river.  
29.05 chains - True point for the special meander cor. on the  
 E & W center line of the NW¼ of sec. 33 at intersection with  
 the adjusted record meander line of the right bank of the  
 Umpqua River. This point falls in the river where it is  
 impractical to establish a permanent monument.