

PRIMARY CORNER DESCRIPTION Wit. Point betw. Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3213)

Marked a Fir 50" dia., from which
A Fir 50" dia., bears N.50°W., 35 lks. dist.
A Fir 30" dia., bears S.50°E., 19 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Setp. 7, 1960 - C.S. File 49/41

Found - Orig. 30" now down 34" Fir, S.50°E., 12.5 ft. I open and find good scribe marks "BT"
Orig. 50" Fir N.50°W., 23.1 ft., now down and mostly rotted. Shows old notch.
Orig. corner tree now down.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
W.C. S 4
S 9
1960

New BTs- 16" Hemlock bears N.30½°W., 48.2 ft. scribed WC S4 CS BT.
13" R.Fir bears S.20°E., 32.8 ft. scribed WC S9 CS BT.

Fd. and used in BLM Resurvey by C. Albert White, Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #515, Surveyed June/Oct. 1963 - (DCSO records Vol. 32 Page(s) 13480-81)

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55 Page(s) 21308-9)

The witness point bet. secs. 4 & 9, monumented with an iron post, 1½" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd from which the remains of BTs mkd. by the DCSO in 1960 reported by White and Beck

A fir, 29" dia., bears S.20°E., 33.0 ft., with a healed blaze.
A decayed fir stump, 18" dia., bears N.30½°W., 48.2 ft. no marks visible. (Record, hemlock)
and new bearing tree
A fir, 7" dia., bears N.24°E., 15.8 ft., mkd. X BT.

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 320579

PRIMARY CORNER DESCRIPTION Wit. Point betw. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

W 1/16 bears: S.89°44'59"W., 0.60 ft
Point for the W 1/16 sec. cor. of secs. 4 and 9 determined
at midpoint longitudally bet. the 1/4 sec. cor. of secs. 4
and 9 and the cor. of secs. 4, 5, 8, and 9.
Set a stainless steel post, 28" long, 2½" dia., 22" in the
ground, with brass cap mkd. T 24 S R 7 W

W 1/16 $\frac{S}{S} \frac{4}{9}$

2003

from which

A hemlock, 14" dia., bears S.10°E., 48.7 ft., mkd. W
1/16 S9 BT.

A fir, 16" dia. bears N.66°W., 5.6 ft. mkd. W 1/16 S4 BT
Deposit a magnet, in a white plastic case, at the base of
the stainless steel post

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag
Nail) driven at the base right side-center, unless
otherwise described in the corner description