

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 340140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979 - (DCSO records Vol. 43 Page(s) 16655-56)

-----  
Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.  
Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:    T 24 S R 7 W  
                                  C 1/4 S 33  
                                  1979

from which  
  A Fir 22" dia., bears N.67½°E., 29 lks. mkd. C ¼ S33 BT.  
  A Yew 10" dia., bears S.24½°W., 45½ lks. mkd. C ¼ S33 BT.

Kent Inman - For: Roseburg Resources Co. - 12/2008 - M158-62

-----  
Found -  3¼" brass cap on a 2½" iron pipe - BLM 1983  
          12" Yew with a partly healed face and BLM BT tag  
                  bears S.24½°W., 30.0'  
          29" G.Fir with a healed face and BLM BT tag bears  
                  N.67½°E., 19.2'  
New -    8" G.Fir bears S.40°E., 45.2' scribed C¼ S33 BT.  
          27" G.Fir bears N.22°W., 14.9' scribed C¼ S33 BT.