

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3206)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.87½°E., 990 lks. dist.
A Fir 50" dia., bears S.89°E., 1000 lks. dist.

Douglas Co. Surveyors Office - John M. Powell - 11/30/1970
(added 7/19/2021) - C.S. File 49/41-60

Reported as not found
Found 1" iron pipe at approx. cor.
BLM has it tagged for their use only!
No trace of large fir BTs on top of ridge 1000 lks east.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15296-97)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

1/4 S 28
S 33
T 24 S R 7 W
1973

from which
A Fir 13" dia., bears N.46½°E., 48 lks. mkd. ¼ S28 BT.
A Fir 15" dia., bears S.50°W., 34 lks. mkd. ¼ S33 BT.
From this corner, a locally established point bears S.89°E., 0.693 chs. dist., monumented with an iron pipe, 1" dia., firmly set, protruding 30" above ground.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #998, surveyed Oct/Nov. 1979 - (DCSO records Vol. 43 Page(s) 16656)

Mark Smalley - For: Scott Timber Co. - Sept. 1996 -M 124-27

Found - 1973 Cadastral brass cap and iron pipe.
13" Fir N.46½°E., 31.7 ft., stump.
22" Fir S.50°W., 22.4 ft., healed.
New BTs- 16" Fir N.10°E., 18.9 ft. scribed ¼ S28 BT.
14" Fir N.88°W., 12.1 ft. scribed ¼ S28 BT.
12" Fir S.17°E., 30.5 ft. scribed ¼ S33 BT.

Fd. Ok by Neil Hibbs - 5/2004 - M145-34
Fd. per rec. 10/2022 - D. Edwards M181-36
Fd. per rec. 10/2023 - B Heichel M183-1