

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3210)

-----  
Set ¼ sec. post, from which  
An Oak 20" dia., bears N.47°E., 66 lks. dist.  
An Oak 24" dia., bears S.45°E., 449 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - July 15, 1960 - C.S. File 49/41-25

-----  
Found both orig. BTs. Both check record distance and bearing. Each was opened years ago. Old faces rotted off. No scribing found. I find 3" x 3" scribed stake (old) at corner, scribed ¼ S. Corner under E-W fence.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 7 W  
¼  $\frac{S\ 21}{S\ 28}$   
1960

New BTs- 26" W.Oak bears N.34°W., 73.3 ft. scribed ¼ S21 CSBT  
11" W.Oak bears S.14°E., 15.2 ft. scribed ¼ S28 CSBT

Survey by Mark Smalley - For: Scott Timber Co. - Sept. 1996 -M 124-27

-----  
Found - DCSO 1960 brass cap and iron pipe.  
38" Oak N.47°E., 43.6 ft., rotted face. (Orig. BT)  
13" Oak S.14°E., 15.2 ft., healed. (1960)  
New BTs- 11" Fir N.55°W., 32.2 ft. scribed ¼ S BT.  
12" Maple S.47°W., 45.1 ft. scribed ¼ S BT.

Fd. OK by C. Sweeden, Sept. 1999 - M133-24  
Carl notes that 38" Oak bears N.47°E., 60.1'

Found OK by C. Sweeden, Aug. 2003 - M142-80  
Found OK by C. Sweeden, 6/2006 M152-34  
Found OK by C. Sweeden, 1/2008 - M155-7  
Fd. per rec. 10/2022 - D. Edwards M181-36  
Fd. per rec. 10/2023 - B Heichel M183-1