

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Pages 3211-12)

Set ¼ sec. post, from which
 An Oak 20" dia., bears N.31°E., 63 lks. dist.
 An Oak 12" dia., bears S.19°W., 16 lks. dist.

Wm. S. Barnes - For: D. Brownson - April 1970 - M 39-51

Prorated corner.
Set 5/8" brass rod for ¼ corner.
New BT - 20" D.Fir S.52°W., 130.6 ft. mkd. T24S R7W ¼ S16 BT

Fd. OK by C. Sweeden, Sept. 1999 - M133-24

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- Aug. 20, 2014 - C.S. File 67/41-52

Found - 1970 5/8" brass rod set plumb and protruding 3" above ground.
No evidence of OBT Oaks remains in area.
A 20" D.Fir now a 42" dia., D.Fir with a fully healed double blaze; bears S.52°W., 130.6 ft. (as per record) 1970
New - A 16" dia., double trunk maple (dia., measured at 3 ft. height) scribed "¼ S16" "CSBT" on a double blaze (upper blaze is at breast height and blazes are on the most westerly trunk); bears N.67°E., 24.5 ft.
A 17" dia. B.Oak scribed "¼ S21 CS" "BT" on a double blaze; bears S.43°E., 25.5 ft.
A 10" dia. D.Fir scribed "¼ S16 CS" "BT" on a double blaze; bears N.71½°W., 26.1 ft.
Note - Monument is on moderate southerly slope in a mixed open forest of older fir, maple, oak and madrone.
Compass decl. 15½°E.