

PRIMARY CORNER DESCRIPTION So. 1/4 Corner for Sec. 33 only, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2462)

Set ¼ sec. post, from which
A Fir 50" dia., bears S.88°E., 6 lks. dist.
A Fir 16" dia., bears N.66°W., 103 lks. dist.

Survey by William Eimstadt - For: International Paper - July 1976 - M 61-14

Set 5/8" x 30" Rebar at corner, from which
24" Fir N.52°50'W., 22.3 ft. "¼ S33 BT"
28" Fir N.32¼°E., 35.8 ft. "¼ S33 BT".

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Aug. 12, 2014 - C.S. File 67/41-46

Found - 1976 5/8" dia., iron rod (rebar) (proportioned) just below ground surface. Iron rod leans S.77°W., 0.4 ft. off of plumb but ground conditions and straightness of rod indicate it was originally set as found. Bearings and distances measured from top of iron rod as found.

No evidence of Orig. BTs.

1976 BTs- A 24" fir now a sawn, rotted 26" dia., 2 ft. tall fir stump with healed blaze evident (blaze opened to find scribing "¼ S33 BT" as per record. This stump bears N.56°W., 23.2 ft. (rec. N.52°50'W., 22.3 ft., a face distance.)

A 28" Fir now a broken and rotted 22" dia., 2 ft. tall fir stump with possible blaze evidence in bark but with all blaze and face evidence rotted away. This stump bears N.34°E., 34.5 ft. (record N.32¼°E., 35.8 ft. a possible slope dist.)

New - A 20" dia. D.Fir scribed "¼ S33 CS" "BT" on a double blaze; bears N.43½°E., 12.3 ft.

An 8" dia. D.Fir scribed "¼ S33" "CSBT" on a double blaze; bears N.84°E., 21.0 ft.

A 20" dia. Grand Fir (trunk is very crooked in its first 6 ft.) scribed "¼ S33 CS" "BT" on a double blaze; bears N.82°W., 58.6 ft.

A 9" dia. D.Fir scribed "¼ S33 CS" "BT" on a double blaze; bears N.38¼°W., 62.2 ft.

Note - Monument is in very old mixed fir reprod. forest and on north edge of old cat road.
Compass decl. 15½°E.