

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3206)

Set post, cor. secs. 27, 28, 33 and 34, from which
 An Oak 12" dia., bears S.55°W., 27 lks. dist.
 A Fir 15" dia., bears S.50°E., 11 lks. dist.
 A Fir 15" dia., bears N.80°W., 95 lks. dist.
 An Oak 24" dia., bears N.12½°E., 512 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3244) and page 3274)

(Page 3244)
 The Sec. cor., which is a post 4" sq., marked T24S S27 on NE.; R7W S34 on SE.; S33 on SW. and S28 on NW. faces, with 1 notch on S. and 3 notches on E. edges, from which
 An Oak 30" dia., bears N.12½°E., 512 lks. dist. mkd. T24S R7W S27 BT.
 A Fir 20" dia., bears S.50°E., 11 lks. dist. mkd. T24S R7W S34 BT.
 An Oak 16" dia., bears S.55°W., 27 lks. dist. mkd. T24S R7W S33 BT.
 A Fir 20" dia., bears N.80°W., 95 lks. dist. mkd. T24S R7W S28 BT.

(Page 3274)
 Cor. to secs. 27, 28, 33 and 34.
 BT bears S.70°E., not S.50°E.
 A W.Oak 30" dia., bears N.20°E., 537 lks. dist. with scars where surveyors marks have been put on and overgrown with new wood.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Aug. 14, 1959 - C.S. File 49/41-24

Found - Orig. 20" now 50" Fir S.70°E., 7.3 ft., I open and find good scribing "B".
 Orig. 20" now 50" Fir N.80°W., 62.7 ft., partly opened, about 10 years ago.
 Remains of large Oak stump that checks bearing and distance for orig. SW. BT.
 No trace of orig. NE. BT found.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	7	W
	S	28		S	27
	S	33		S	34
				1959	

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- Rescribe orig. S.70°E., 8.0 ft., 50" Fir scribed S34 T24S R7W CS BT.
8" W.Fir bears S.52°W., 32.9 ft. scribed S33 T24S R7W CS BT.
20" R.Fir bears N.78°W., 47.0 ft. scribed S28 T24S R7W CS BT.
No trees near to NE.

Fd. and used in BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15294)