

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3207)</p> <p>-----</p> <p>Set ¼ sec. post, from which              A Maple 7" dia., bears S.30°W., 19 lks. dist.              A Fir 30" dia., bears N.30°E., 20 lks. dist.</p>
<p>Looked for not found, DCSO, June 5, 1990 - C.S. File 64/9-7</p>
<p>Survey by James Artman, LS #2268 - For: D. Ocumpaugh - Nov. 1990 - M 111-1 and C.S. File 63/101</p> <p>-----</p> <p>Found - Root hole of original BT, bears S.30°E., 12.5 ft.              Set 5/8" x 30" Iron rod with cap mkd: "ARTMAN RLS 2268", from which              10" Myrtle bears N.20°W., 22.9 ft. scribed ¼ S21 BT.              15" D.Fir bears N.26°E., 23.5 ft. scribed ¼ S22 BT.              10" D.Fir bears S.08°30'E., 56.3 ft. scribed ¼ S21 BT.              40" Maple bears S.60°W., 3.1 ft. scribed ¼ S21 BT to a 60d spike in side.</p>
<p>Fd. OK, May 1996 by Degroot - 1996-0051</p>
<p>Carl Sweeden - For: Don Ocumpaugh - 8/2005 - 2005-0084 A&amp;B</p> <p>-----</p> <p>Found - 5/8" I. ROD W/ YPC "ARTMAN" AND BT's as follows              10" myrtle, N.20°W., 43.6' (rec. 22.9') scribe partly vis., tag              15" now 17" D.Fir stump, N.24°E., 23.5', scar vis., tag, 3' tall              10" now 12" D.Fir, S.4°E., (rec. S. 8½°E) 56.3', Scar vis., tag              40" maple, S.60°W., 3.1', scar vis., tag</p>
<p>Ronald L. Rice, Ward NW - July 30, 2010 - C.S. File 65/69-47</p> <p>-----</p> <p>Found - 1" plastic cap marked "ARTMAN RLS 2268" on 5/8" rebar with the following accessories:              13" D.Fir bears S.8½°E., 56.3' - healed face              10" Maple bears N.23½°W 42.3' (record Myrtle bearing N.20°W., 43.6') - scribing visible              18" D.Fir stump bears N.24°E., 23.5' - healed face              Record 40" Maple bearing S.60°W., 3.1' - down and removed 5/8" rebar with 1" plastic cap marked "ARTMAN RLS 2268" bears N.0°39'50"E., 144.53' (record N.0°53'23"E., 144.97')</p> <p>Note - Corner has steel post adjacent to it. All BTs have red painted bands &amp; yellow tags.</p>