

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3208)

Set post, cor. secs., from which
An Oak 12" dia., bears S.60°E., 170 lks. dist.
An Oak 12" dia., bears N.50°E., 188 lks. dist.
An Oak 12" dia., bears N.1°W., 645 lks. dist.
An Oak 24" dia., bears S.5°W., 511 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3270)

The Sec. cor., which is a post 4" sq., mkd. T24S S15 on NE.; R7W S22 on SE.; S21 on SW.; and S16 on NW. faces, with 3 notches on S. and E. edges, from which
An Oak 18" dia., bears N.50°E., 186 lks. dist. mkd. T24S R7W S15 BT.
An Oak 18" dia., bears S.60°E., 170 lks. dist. mkd. T24S R7W S22 BT.
An Oak 30" dia., bears S.5°W., 511 lks. dist. mkd. T24S R7W S21 BT.
An Oak 18" dia., bears N.1°W., 645 lks. dist. mkd. T24S R7WS16 BT.

Douglas Co. Surveyors Office - N.E. Richardson - Wit: Les Kershner; M.E. Godfrey - Dec. 9, 1946 - C.S. File 38/13

Found one old BT, S.5°W., 511 lks.
Found two dead and down trees that checked for dist. & brg.
Marked a 6" Fir for corner, from which
Fir 30" dia., N.43°E., 20.6 ft.
Fir 20" dia., S.55½°E., 25.2 ft.
W.Oak 12" dia., S.57°W., 18.4 ft.
Fir 36" dia., N.50°W., 85.3 ft.

Douglas Co. Surveyors Office - John M. Powell, W. Penley, crew - Dec. 10, 1970 - C.S. File 49/41-66

Found - 6" now 11" D.Fir corner tree.
30" now 38" D.Fir, N.43°E., 20.6 ft., bark scribe visible, faint "BT S15".
36" now 39" D.Fir, N.50°W., 85.3 ft., bark scribe visible "S16 CS BT"
12" now 16" W.Oak S.57°W., 18.4 ft., shows good scar
20" D.Fir, now stump, S.55½°E., 25.2 ft.
Set Brass cap at cor. mkd:

(Cont. Next Page)

