

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3209)

Set ¼ sec. post, from which
A Fir 24" dia., bears S.50°E., 31 lks. dist.
A Fir 6" dia., bears S.2°W., 45 lks. dist.

Survey by Bruce Shaner - For: Woodward & Dickerson - June 1996 - M 125-20; C.S. File 65/2-12 A-C

Set by proportionate measurement. Set a 3" alum. cap on a 2½" x 30" alum. pipe, from which a
40" Red Cedar scribed "¼ S15 BT" bears S.26°E., 32.4 ft.
36" Red Cedar scribed "¼ S15 BT" bears N.62°E., 45.6 ft.
12" Red Cedar scribed "¼ S16 BT" bears S.17°W., 24.6 ft.
6 ft. steel fence post bears S.40°W., 1.0 ft.
6 ft. steel fence post bears S.10°E., 1.4 ft.
A 6 ft. wide stream, flowing East, is North, 35.0 ft. from ¼ section. (Nice hike downhill to this corner.)

Fd. Ok by C. Sweeden, Aug. 1997 - M 124-61
Fd. OK by C. Sweeden, Jan. 2000 - M134-10
Fd. OK by C. Sweeden, Feb. 2001 - M136-63