

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Pg 3209)

Set post cor. secs. 9, 10, 15 and 16, from which

- A Fir 12" dia., bears S.73°W., 15 lks. dist.
- A Fir 15" dia., bears N.73°W., 23 lks. dist.
- A Fir 18" dia., bears N.73°E., 17 lks. dist.
- A Fir 15" dia., bears S.55°E., 37 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3252)

The post and one of the original bearing trees being gone, I re-establish the cor. as follows:
Set a post 4 ft. long, 4" sq., 24" in the ground, marked T24S S10 on NE.; R7W S15 on SE.; S16 on SW.; and S9 on NW., faces with 4 notches on S. and 3 notches on E. edges, from which

- A Fir 24" dia., bears N.73°E., 17 lks. mkd. T24S R7W S10 BT.
- A Fir 20" dia., bears S.55°E., 37 lks. mkd. T24S R7W S15 BT.
- A Cedar 50" dia., bears S.73°W., 27 lks. mkd. T24S R7W S16 BT.
- A Fir 20" dia., bears N.73°W., 23 lks. mkd. T24S R7W S9 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Jan. 25, 1956 - C.S. File 47/91

Corner renewed from original BT, a 15" now 30" Fir, S.55°E., 24.4 ft. BT is down. Found bark scribe "S15" in good condition. No other BTs found.
Set iron pipe with brass cap at corner, marked:
Douglas County Surveyor Office
T 24 S R 7 W
S 9° S 10
S16° S 15
1956

Blazed and scribed:

- 8" R.Fir S.32°E., 37.3 ft. mkd. S15 CS BT.
- 56" Cedar snag, S.89°W., 24.0 ft. mkd T24S R7W S16 CS BT
- 10" W.Fir, North, 38.8 ft. mkd. S9 CS BT.
- 16" W.Fir N.40°E., 35.0 ft. mkd. S10 CS BT T24S R7W.

continued next page

1

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK April 1996 by L. Roberts - M 123073

Survey by Bruce Shaner - For: Woodward & Dickerson - June 1996 - M 125-20; C.S. File 65/2-12 A-C

Found - Brass cap set by County in 1956.
56" Cedar BT, now windfall, bears S.89°W., 24.0 ft
24" W.Fir BT, face grown over, bears North 33.8 ft
26" W.Fir BT, face grown over, bears N.40°E. 34.0'
New - 8" W.Fir scribed "T24S R7W S16 BT" bears S.63°W.,
24.3 ft.
14" D.Fir scribed "T24S R7W S15 BT" bears S.32°E.,
30.3 ft.
6 ft. steel fence post, I set, bears South 1.0 ft.
End of US BLM road #24-7-9.0 bears N.30°W., 200 ft. from
corner.

Fd. Ok by C. Sweeden, Aug. 1997 - M 124-61
Fd. OK by C. Sweeden, Jan. 2000 - M134-10
Fd. OK by C. Sweeden, Feb. 2001 - M136-63

Carl Sweeden - July 31, 2003 - C.S. File 65/48-2

Found - 2½" brass cap - 1956 DCS0
Cedar snag BT, S.89°W. 24.0' to root hole, rotting
- DCS0 1956
24" W.Fir BT, bears North 33.8' scar vis., tag -
DCS0 1956
24" W.Fir BT, bears N.40°E., 34.0' scar vis. tag -
DCS0 1956
8" W.Fir S.63°W., 24.3' to root hole, laying down,
tag - Shaner 1996
15" D.Fir S.32°E. 30.3' scar vis tag - Shaner 1996
Reset - 6' "T" post 1.0' East.
New - 16" W.Fir S.76°W. 34.70' scribed "NE S 16 BT", tag

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2037, surveyed Feb/March 2003 - (DCS0 rec. Vol. 55 Page(s) 21298-9)

The cor. of secs. 9, 10, 15, & 16, perpetuated by the DCS0 in 1956, & further perpetuated by Shaner, in 1996, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd., from which the remains of an original BT

A roothole bears S.55°E., 24.4 ft with fallen fir trunk, 56" dia., lying alongside, no marks visible.

Continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and remains of bearing trees mkd. by the DCSO
A fir, 25" dia., bears N.36°E., 33.3 ft., with a healed blaze.
A roothole bears S.89°W., 24.0 ft., with fallen cedar trunk, size indeterminate, lying alongside, no marks visible.
A fir, 24 " dia., bears N.1½°W., 33.2 ft., with a healed blaze.
and remains of bearing trees mkd. by Shaner
A fir, 14" dia., bears S.32°E., 30.3 ft., with a healed blaze.
A roothole bears S.60°W., 24.3 ft., with fallen trunk, 9" dia., lying alongside, species indeterminate, with a healed blaze.