

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCS0 records Vol. 8 Page(s) 3256)

-----  
This point falling on a flat rock in place, I mark a cross (+) at exact cor. point for cor. to secs. 3, 4, 9 and 10, with 5 notches on S. and 3 notches E., from cor. point  
A Fir 5" dia., bears N.41°E., 61 lks. dist. mkd. T24S R7W S3 BT.  
A Fir 30" dia., bears S.67°E., 26 lks. dist. mkd. T24S R7W S10 BT.  
No tree convenient in sec. 9.  
A cross (+) marked on a perpendicular rock marked S9, bears S.68½°W., 7 lks. dist.  
A Fir 5" dia., bears N.3°W., 37 lks. dist. mkd. T24S R7W S4 BT.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCS0 records Vol. 8 Page(s) 3279) and Page 3280)

-----  
(Page 3279)  
Intersect 137 lks. N. of original cor. to secs. 3, 4, 9 and 10, and 180 ft. above stream.  
I set a sandstone 30x16x10 ins., 23" in the ground for C C to secs. 3 and 10, marked CC on W., with 3 notches on E. and 5 notches on S., from which  
A Fir 16" dia., bears N.55°E., 22 lks. dist., marked T24S R7W S3 CC BT.  
A Fir 8" dia., bears S.47°E., 92 lks. dist. mkd. T24S R7W S10 CC BT.  
A Fir 14" dia., bears S.60°W., 20 lks. dist. mkd. T24S R7W S3 and 10 CC BT.  
I destroy original cor. to secs. 3, 4, 9 and 10.  
(Page 3280)  
Intersect at closing cor. to secs. 3 and 10.  
I therefore make the same cor. to secs. 3, 4, 9 and 10, by removing CC from cor. stone and bearing trees, S3 and 10 from the SW. BT, and marking S9 on same.  
A Fir 40" dia., bears N.34°W., 52 lks. dist. which I mark T24S R7W S4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Nov. 29, 1957 - C.S. File 49/41-1

-----  
Found - 30"x16"x10" sandstone at corner, 18" out of ground. Checks record for size but I cannot find any notches I am sure of. (Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. 8" now 12" Fir rotted stump S.47°E., 60.7 ft.,  
no scribing found.  
Orig. 14" now 24" Fir, down. I open and find scribe  
marks S.60°W., 13.2 ft.  
Orig. 40" now 50" Fir, shows good scar. I do not  
open, N.34°W., 34.3 ft.  
Orig. 16" now 26" Fir, N.55°E., 14.5 ft., shows good  
scar. I do not open.  
All BTs check record dist. and brg.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 7 W  
S 4 | S 3  
S 9 | S 10  
1957  
New BTs- 12" R.Fir bears S.30°W., 28.2 ft. scribed S9 T24S  
R7W CS BT.  
4" Hemlock bears S.75°E., 26.0 ft. scribed S10 T24S  
R7W CS BT.  
The orig. NE. and NW. BTs alive & in good condition.

Fd. OK, April 1996 by L. Roberts - M 123-73

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under  
Group #2037, surveyed Feb/March 2003 - (DCSO rec. Vol. 55  
Page(s) 21300-1)  
-----  
The cor. of secs. 3, 4, 9, & 10, perpetuated by the DCSO, in  
1957, monumented with an iron post, 1¼" dia., firmly set,  
projecting 15" above ground, with brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A fir, 36" dia. bears N.55°E., 14.5 ft with a healed blaze  
A decayed fir stob, size indeterminate, 6 ft. high, bears  
S.69¾°W., 12.3 ft., with scribe marks BT visible on  
decayed blaze. (Record, S.60°W., 13.2 ft.)  
A roothole bears N.39¾°W., 34.3 ft., with fallen fir  
trunk, size indeterminate, lying downhill, no marks  
and BTs mkd. by the DCSO  
A hemlock, 15" dia., bears S.73½°E., 26.0 ft with a healed  
double blaze.  
A fir, 26" dia., bears S.30°W., 28.2 ft., with a healed  
double blaze.  
and a new bearing tree  
A hemlock, 5" dia., bears N.36¾°W., 39.4 ft., mkd. X BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center, unless otherwise  
described in the corner description