

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3258)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 3" dia., bears N.72°E., 3½ lks. dist. mkd. ¼ S BT.
A Fir 4" dia., bears N.68°W., 7 lks. dist. mkd. ¼ S BT.

Survey by William Eimstad - For: International Paper Co. - July 1976 - M 61-14

Set 5/8" x 30" Rebar at corner, from which
22" Fir N.26°W., 28.6 ft. "¼ S4 BT"
12" Fir S.53°E., 7.4 ft. "¼ S3 BT"
Corner is 28 ft. East of ridge.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Aug. 15, 2014 - C.S. File 67/41-49

Found - 1976, 5/8" dia., iron rod is set plumb, protruding 2" above ground.
Stumps in the area were searched for orig. BT evidence, none was fd.
1976 BT- A 12" Fir now a 23" dia., D.fir with a fully healed single blaze; bears S.53°E., 7.4 ft.
The other 1976 BT position falls in an excavated log landing, no evidence remains.
New - An 8" dia. D.fir scribed "¼ S3 CS" "BT" on a double blaze; bears N.21¼°E., 22.7 ft.
A 6" dia. D.fir scribed "¼ S4 CS" "BT" on a double blaze; bears S.37½°W., 7.5 ft.
A 5" dia. D.fir scribed "X" "CSBT" on a double blaze; bears N.39¾°W., 11.8 ft.
Note - Monument is near SE corner of old logging landing at end of a forest spur road and at top of a very steep west slope.
Old growth timber to south, young reprod fir to north.
Compass decl. 15½°E.