

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 400676

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 3

Alias 868791 Description M.C. on left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3258)

Intersect the left bank of Umpqua River. At which point I set a post 4 ft. long, 4" sq., 24" in the ground for meander cor. to fractional secs. 3 and 4, marked MC on N.; S3 on E.; T24S R7W on S.; and S4 on W. faces, from which
A Maple 14" dia., bears S.33°W., 26 lks.dist. mkd. T24S R7W S4 MC BT.
A Myrtle 24" dia., bears S.1½°E., 90 lks. dist. mkd. T24S R7W S3 MC BT.
(On pages 3277-78, Whipple runs line again giving distances between corners - no other information regarding this corner description. V.Laugen, Feb. 1997)

Survey by William A. Eimstad - For: International Paper Co. July 1976 - M 61-14

Set 5/8"x30" Rebar in riprap at edge of county rd., from which
21" Myrtle S.67°E., 53.2 ft. "T24S R7W S3 MC BT"
15" Myrtle N.29°W., 17.6 ft. "T24S R7W S4 MC BT"
Corner is 22 ft. from traveled center line of county road. Top of river bank 69 ft. North.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell, crew - Jan. 6, 1982 - C.S. File 61/30-8

Found - 5/8" x 30" I.R. set in rip-rap should of road.
21" Myrtle with scribed "T24S R7W S3 MC BT" visible in unhealed blaze, bears S.67°E., 53.2 ft.
15" now 18" Myrtle with scribed "T24S R7W S4 MC BT" visible in unhealed blaze bears N.29°W., 17.6 ft.
Being unable to set standard Iron pipe/brass cap monument in rip-rap shoulder, I placed 1¼" dia. alum. cap on found 5/8" Iron rod. and marked it "Douglas Co. MC 4 3 1982 Surveyor".
(Sketch in C.S. File)

Fd. OK, April 1994 by L. Dolan - M 122-20
Fd ok by Mark Smalley - 6/1998 - M 129-30

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Aug. 1, 2014 - C.S. File 67/41-38

Found as described in 1982. BT tags were interchanged, we remove tags and place on correct trees. Compass decl. 15½°E.