

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3245)

-----  
A point about 650 ft. below top of mountain and Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on N. face, from which  
A Fir 6" dia., bears N.70°E., 31 lks. dist. mkd. ¼ S BT.  
A Fir 18" dia., bears S.41°E., 21 lks. dist. mkd. ¼ S BT

Clifford M. Bryden - April 1960 - M 18-5

-----  
Set corner at proportionate distance, 5/8" x 18" square head bolt with "X" on head set 1 ft. below surface in East shoulder of road, from which scribed  
30" D.Fir S.56°E., 14.55 ft.  
6" D.Fir N.61°E., 22.72 ft.

Fd. OK by D.Edwards, Sept. 1998 - M130-26

Found OK by M. Smalley, May 2003 - M142-29