

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3248)

A point about 650 ft. above Lost Creek and set a post, 3' sq., 3 ft. long, 24" in the ground for ¼ sec. cor., marked ¼ S on N. face, from which
 A Fir 14" dia., bears S.45°E., 63 lks. dist. mkd. ¼ S BT
 A Chinquapin 10" dia., bears N.23°W., 45 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Milo Godfrey and crew - C.S. File 49/41-56 - Feb. 1966

Corner searched for, not found.

David Edwards, surveyed for E. Valance and Roseburg Resources, Sept. 1998 - M130-26

Set at proportionate position - 5/8" x 48" I. rod w/alum cap.
New Accessories -
 9" dia. Fir, bears S.47°E., 13.92 ft.
 8" dia. Fir, bears S.16°E., 10.78 ft.
 18" dia. Fir, bears S.77°W., 8.13 ft.
 8" dia. Fir, bears N.33°W., 8.08 ft.
Note - Bearing trees were scribed according to the 1973 manual, measured to center of tree at root crown.