

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3252 and Page 3276)

(page 3252)

40.00 chs. Set temp. ¼ sec. cor.

(page 3276)

I destroy ¼ sec. cor. and at 37.34 chs. which is in the middle of this line, I Set a post, 4" sq., 4 ft. long, 24" in the ground for ¼ sec. cor. mkd. ¼ S on N., from which

A Laurel 24" dia., bears N.57°W., 23 lks. dist. mkd. ¼ S BT.

A Cedar 4" dia., bears S.7°W., 20 lks. dist. mkd. ¼ S BT.
June 15, 1896

Survey by Les Roberts - For: I.P. Timberlands - April 20, 1996 - M 123-73

Set 3/4" x 24" alum. rod with 3¼" alum. cap. (Buried purple magnetic marker under 24" alum. rod.)

New BTs- 6" Fir S.6°W., 18.2 ft., scribed & painted red.

12" Fir N.36°E., 39.5 ft. scribed & painted red.

18" Fir N.73°E., 21.1 ft. scribed & painted red.

26" Fir, S.78°E., 6.1 ft. scribed and painted red.

Fd. Ok by C. Sweeden, Aug. 1997 - M 124-61

Fd. OK, Feb. 2001 by C. Sweeden - M136-63

Carl Sweeden - July 31, 2003 - C.S. File 65/48-1

Found - 3¼" alum. cap.

6" Fir S.6°W., 18.2', dbl blaze, scribe vis. tag.

12" Fir N.36°E., 39.5'. dbl blaze, scribe vis. tag.

18" Fir N.73°E., 21.1' dbl blaze, scribe vis. tag.

26" Fir, S.78°E., 6.1' dbl blaze, scribe vis. tag.

All by Roberts in 1996

3/4" IP S.71°E. 4.27' @ base of 33" D.Fir **-NO RECORD**