

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3278-79)

Set post 4" sq., 4 ft. long, 24" in the ground for ¼ sec. cor., marked ¼ S on N., from which
 A Fir 10" dia., bears S.89°W., 86 lks. dist. mkd. ¼ S BT.
 A Fir 50" dia., bears N.60°E., 58 lks. dist. mkd. ¼ S BT.
I destroy old ¼ sec. cor. and continue W.
(Note: On DCSO records, page #3256, Whipple set a "temp. ¼ sec. cor." I found no other notes regarding another previous corner. V. Laugen 2/1997)

Survey by Les Roberts - For: I.P. Timberlands - April 20, 1996 - M 123-73

Set 3/4" x 40" alum. rod with 3¼" alum. cap. Buried purple magnetic marker under 24" alum. rod, from which new BTs:
 5" Maple S.13°E., 19.1 ft., scribed/painted red.
 12" Fir S.68°E., 10.5 ft., scribed/painted red.
 14" Fir N.51°E., 34.2 ft., scribed/painted red.
 18" Fir, North, 20 ft., scribed/painted red.