

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3243)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 26, 27, 34 and 35, marked T24S S26 on NE.; R7W S35 on SE.; S34 on SW.; and S27 on NW. faces, with 1 notch on the S. and 2 notches on E. edges, from which

- A Fir 24" dia., bears N.33°E., 174 lks. dist. mkd. T24S R7W S26 BT.
- A Fir 36" dia., bears S.48°E., 127 lks. dist. mkd. T24S R7W S35 BT.
- A Cedar 36" dia., bears S.85°W., 154 lks. dist. mkd. T24S R7W S34 BT.
- A Fir 40" dia., bears N.50°W., 147 lks. dist. mkd. T24S R7W S27 BT.

J. C. Cole, Surveyor - Wit: L.W. Harris; Jack Sabonijian; Loy Harris; Jim Evans - Jan. 18, 1924 - Vol. 3 Page 177

I renewed this corner from the remains of the original BTs as follows:

I set a Cedar BT which is standing alive and bearing scribe marks, thence N.85°E., 101.6 ft. and from this point

- A burned out stump N.50°W., 97.0 ft.
- A stump 24" dia., N.33°E., 112.0 ft.
- A hole where tree had burned out, S.48°E., 80 ft.

I set a sandstone 10" x 10" x 15" marked C.S. on North and X on top, 2 notches on East and one on South and made mound of rock. No trees suitable for bearing trees.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Aug. 1959 - C.S. File 49/41-23

Found - Orig. 36" now 48" Cedar S.85°W., 101.6 ft., center rotted, no scribing found, shows old blaze and axe marks.

Now 36" partly rotted Fir snag, checks record distance and bearing for orig. NE. BT, no scribing found.

Stump hole that checks brg & dist. for orig. NW. BT. No trace of original SE. BT found.

Find 10" x 14" x 6" sandstone out of ground but at corner, marked with 2" + on top and C.S. on face.

Set Brass cap at cor. mkd: County Surveyors Office 1959

T	24	S	R	7	W
	S	27		S	26
	S	34		S	35

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Reset corner stone alongside brass cap.
New BTs- 12" R.Fir, N.15°W., 15.2 ft. "S27 T24S R7W CS BT"
 14" R.Fir, N.49°E., 40.6 ft. "S26 T24S R7W CS BT"
 14" R.Fir, S.59°W., 38.8 ft. "S34 T24S R7W CS BT"
 8" Laurel, S.74°E., 41.5 ft. "S35 T24S R7W CS BT"

Found OK by M. Smalley, May 2003 - M142-29