

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3245 and 3275)

(Page 3245)
Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
 A Fir 30" dia., bears N.24°E., 60 lks. dist. mkd. ¼ S BT
 A Fir 18" dia., bears S.60°W., 33 lks. dist. mkd. ¼ S BT
(Page 3275)
Post plainly marked ¼ S. (June 16, 1896)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew - B. Bright & T. Watts, BLM, wit. - Feb. 1966 - C.S. File 49/41-57

Found - Orig. 18" now 34" Fir, S.60°W., 21.8 ft., previously opened and shows "¼S" scribe, alive.
 Orig. 30" now 48" Fir, N.24°E., 39.6 ft., down and out of place, several cruiser's marks on bottom side.
Set Brass cap at cor. mkd: County Surveyors Office
 T 24 S R 7 W
 S 27 | S 26
 1966
New BTs- 17" D.Fir N.23°E., 61.6 ft. mkd. ¼ S26 CS BT.
 16" W.Fir S.32°W., 18.3 ft. mkd. ¼ S27 CS BT.
Corner is approx. 50 ft. North of small creek, course West.

Fd. OK by D.Edwards, Sept. 1998 - M130-26