

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec Cor for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3245-46)

A point about 150 ft. below top of spur, Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 22, 23, 26 and 27, marked T24S S23 on NE.; R7W S26 on SE.; S27 on SW.; and S22 on NW. faces, with 2 notches on S. and E. edges, from which

- A Laurel 8" dia., bears N.30°E., 29 lks. dist. mkd. T24S R7W S23 BT.
- A Fir 8" dia., bears S.68°E., 87 lks. dist. mkd. T24S R7W S26 BT.
- A Fir 20" dia., bears S.71°W., 30 lks. dist. mkd. T24S R7W S27 BT.
- A Fir 10" dia., bears N.61°W., 24 lks. dist. mkd. T24S R7W S22 BT.

Douglas Co. Surveyors Office - V.R. Tracey, Mike Stone, J. Layne, crew - Wit: B. Bright and T. Watts, BLM - Feb. 2, 1966 - C.S. File 49/41-55

Found - Orig. 20" now 44" Fir S.71°W., 19.8 ft., shows very old bark scribe, mostly fragmentary "S or 2".
Laurel remnants and stump hole, N.30°E., 19.1 ft., no scribe found.

Stump holes for other 2 orig. BTs, gone completely.
Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 7 W
S 22 | S 23
S 27 | S 26
1966

- New BTs- 24" D.Fir N.47°E., 43.3 ft. mkd. T24S R7W S23 CSBT
6" W.Fir S.58°E., 28.4 ft. mkd. S26 CS BT.
9" W.Fir N.36°W., 7.5 ft. mkd. T24S R7W S22 CS BT.
11" D.Fir S.44°W., 58.1 ft. mkd. T24S R7W S27 CS BT

Fd. and used in BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15290-91)

- Fd. OK by D. Edwards, Sept. 1998 - M130-26
- Fd. Ok by Ronald Quimby, 2/2001 - C.S. File 65/36-4
- Fd. Ok by C. Sweeden, 8/2005 - 2005-0084 A&B