

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3249)

 Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
 A Fir 12" dia., bears N.53°E., 7 lks. dist. mkd. ¼ S BT.
 A Fir 20" dia., bears N.60°W., 11 lks. dist. mkd. ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15293-94)

 Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
 1/4
 S 22 | S 23
 T 24 S R 7 W
 1973

from which
 A Fir 16" dia., bears N.86°E., 20½ lks. dist. mkd. ¼ S23 BT.
 A Fir 17" dia., bears N.24½°W., 59 lks. dist. mkd. ¼ S22 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - June 4, 1990 - C.S. File 64/9-8

 Found - A 3¼" dia. 1973 BLM brass cap on a 2¼" O.D. Iron pipe protruding 6" above ground.
 16" now 20" dia. D.Fir with a fully healed single blaze bears N.86°E., 13.5 ft. (agrees w/rec)
 17" now 18" dia. 5 ft. high D.Fir stump with a fully healed single blaze, bears N.24½°W., 38.9 ft. (agrees w/rec)
 New BTs- 6" dia. Madrone, bark scribed "¼ S23 CS BT" bears S.11½°E., 33.1 ft.
 7" dia. D.Fir, double blazed and scribed "¼ S22 CS BT" bears N.49½°W., 31.6 ft.
 8" dia. D.Fir double blazed and scribed "¼ S22 CS BT" bears S.87½°W., 25.2 ft.

Fd. OK, May 1996 by K. DeGroot - 1996-0051
 Fd. Ok by C. Sweeden, 8/2005 - 2005-0084 A&B