

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500460

PRIMARY CORNER DESCRIPTION Wit. Point on line betw Secs 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3201)

Set post, from which
A Laurel 12" dia., bears S.60°E., 8 lks. dist.
A Fir 12" dia., bears N.45°W., 25 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3249-50)

At the witness cor. bet. secs. 14 and 15, which is 60 chs. N. of cor. to secs. 14, 15, 22 and 23, I find remains of old post, from which (Note: Hathorn describes this same cor. at 80 chs.) V.Laugen, Feb. 1997

A Laurel stump 14" dia., bears S.60°E., 8 lks. dist.
A Fir stump 16" dia., bears N.45°W., 25 lks. dist.
The mark on same, and old post, being obliterated, I destroy all trace of old cor. and reestablish it as follows:
Set a post 4" sq., 24" in the ground mkd. WC on N.; R7W S14 on E.; T24 on S.; and S15 on W. faces, from which
A Fir 36" dia., bears S.51°E., 29 lks. dist. mkd. T24S R7W S14 W C BT.
A Fir 50" dia., bears N.79°W., 83 lks. dist. mkd. T24S R7W S15 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 10, 1958 - C.S. File 49/41

Found both BTs as recorded by Whipple:
30" now 48" Fir S.51°E. I find bark scribing "B" on old axed face.
48" now 50" Fir N.79°W. Checks bearing and distance. Base covered by large stone. No scribing found.
Also found mound of stone at corner and Whipple's scribed stake at corner, scribed W.C.
Set brass cap in mound of stone at corner, mkd: County Surveyors Office 1958 Wit. Cor. S15|S14 T24S R7W.
I rebark scribe:
The 48" Fir S.51°E., 19.1 ft. "W.C. S14 CS BT".
I chisel 2" + and W.C. on SE. face of stone, 8 ft. high, 4 ft. across. Face is slight overhang and faces to SE.
Chisiled + and W.C., 5 ft. above ground, bears N.11½°W., 34.6 ft.

Fd. OK, Jan. 1973 by B. Shaner - M 49-6
Fd. Ok by C. Sweeden, Aug. 1997 - M 124-61

Cont.

PRIMARY CORNER DESCRIPTION Wit. Point on line betw Secs 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- Aug. 18, 2014 - C.S. File 67/41-50

Found - 1958 2½" dia. brass cap (properly mkd) on a 1" I.D. iron pipe leaning south 0.5 ft. (down slope) off of plumb. Monument protrudes 10" above a rough mound of stone. All accessories are measured from plumb position of FD BC monument.

No evidence remains of Orig. BTs.

1893 BTs- A fir 36" dia., now a 55" dia., 2 ft. tall sawn fir stump with no remaining blaze or bark scribing; bears S.51°E., 19.1 ft. (as per rec.)

A fir 50" dia., now a shattered 3 ft. tall fir stump which was once at least 50" in dia., has no blaze or scribing evidence remaining. This stump bears N.79°W., 54.8 ft. (as per record)

1958 BT- A 2x2" chiseled "+" and a 1¼" tall "WC" in a rock face (as previously described) the "+" bears N.14½°W., 33.4 ft. (record N.11½°W., 34.6 ft.)

New - Steep site and nature of fd stone mound indicate monument has tilted downhill. BC monument is returned to plumb and mound of stone is stabilized. Monument now protrudes 9" above stone mound.

A 5" dia. Madrone scribed "X" "CSBT" on a double blaze; bears N.48°E., 3.4 ft.

A 21" dia., D.Fir scribed "WC 14 CS" "BT" on a double blaze; bears S.75¼°E., 25.4 ft.

A 17" dia. D.Fir scribed "WC S15" "CSBT" on a double blaze; bears N.60½°W., 12.3 ft.

A 1¼"x1¼" green and white painted steel fence post protruding 3 ft. above ground (of unknown origin) bears N.30°E., 1.0 ft.

Note - Monument is on steep south slope in old natural reprod. mixed forest. Monument is approx. 100 ft. north from the centerline of Cougar Creek Co. Rd. #57C

Compass decl. 15½°E.