

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3254)

Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Cedar 18" dia., bears N.64°W., 102 lks. dist. mkd. ¼ S BT.
A Yew 9" dia., bears N.80°E., 91 lks. dist. mkd. ¼ S BT.

G. Robert Lecklider - Feb. 28, 1957 - C.S. File 42/232-1

Found no evidence of corner post.
Found - 14" Yew, N.80°E., 91 lks., badly rotted.
36" Cedar, N.64°W., 102 lks., down.
Set 12" x 12" x 14" stone with a "+" on top for the corner, from which
12" Cedar bears N.65°W., 6.4 ft. mkd. ¼ S10 BT.
14" Hemlock bears S.57°30'E., 30.5 ft. mkd. ¼ S11 BT. This tree forks at about 30 ft.
All faces were painted with orange paint.

Fd. OK, April 1996 by L. Roberts plus a 1994 BLM brass cap - M 123-73

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19834)

From the ¼ sec. cor. of secs. 10 & 11, perpetuated by Lecklider, in 1957; monumented with a stone, 14x12x8", firmly set, projecting 6" above ground, with top mkd. X, from which the remains of the original bearing trees:
A yew, 18" diam., bears N.80°E., 96 lks., with healed blaze. (Record, 91 lks.)
A roothole, bears N.64°W., 102 lks., with down cedar alongside, 36" diam., no marks visible.
and bearing trees mkd. by Lecklider
A hemlock, 28" diam., bears S.57½°E., 45 lks., with healed blaze.
A cedar, 24" diam., bears N.65°W., 9½ lks., with healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" diam., 10" in the ground to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd. continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T24S R7W S 10 ^{1/4} S 11 1994</p> <p>Deposit stone alongside the stainless steel post.</p>