

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3203)

Set ¼ sec. post, from which
A Fir 24" dia., bears S.60°W., 63 lks. dist.
A Maple 15" dia., bears S.70°E., 45 lks. dist.

Arthur Evans - Wit: Milo Godfrey; Gene Johnson - Nov. 11, 1954 - C.S. File 41/334

Set by proportional measurement.
Set a 4" x 4" x 48" Fir stake.
Blazed and scribed 2 BTs:
10" Myrtle S.85½°W., 25.1 ft. mkd. ¼ S3 BT RE 2741.
9" Myrtle N.36½°E., 52.8 ft. mkd. ¼ S2 BT RE 2741.

Douglas Co. Surveyors Office - James Byron, Deputy - Ray Irving, chainman - May 25, 1955 - C.S. File 46/24

Found both BTs as set by Evans, 1954, and 4" x 4" stake.
Set a 1" Iron pipe with brass cap at corner, marked "County Surveyors Office T24S R7W ¼ S3 | S2 1955".

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1967 - C.S. File 54/55-3

Found 1955 DCSO brass cap in mound of stone on right bank of creek. Reset by OSHD. (See attached letter and sketch in C.S. File) BTs gone.
Marked new BTs:
15" D.Fir N.43°W., 128.7 ft. mkd. ¼ S3 CS BT.
7" D.Fir S.55°E., 173.0 ft. mkd. ¼ S2 CS BT.
Set steel fence post alongside brass cap.
Corner lies 10 ft. N. of creek, course NW.

Fd. OK, July 1980 by Charles Guile - M 79-52