

PRIMARY CORNER DESCRIPTION C C for Secs. 22 & 23 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3248)

At intersection E. and W. section line, 152 lks. E. of cor. to secs. 14, 15, 22 and 23, at which point, I Set a sandstone 14x10x8 ins., 10" in the ground for closing cor. to secs. 22 and 23, marked C C with 3 notches on S. and 2 notches on E. edges, from which

- A Fir 24" dia., bears S.69°E., 142 lks. dist. mkd. T24S R7W S23 BT.
- A Fir 50" dia., bears S.66°W., 79 lks. dist. mkd. T24S R7W S22 BT.
- A Fir 12" dia., bears N.20°E., 77 lks. dist. mkd. T24S R7W CC S22 and 23 BT.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15292)

The original closing cor. of secs. 22 and 23, on the S. bdy. of sec. 14, determined at record bearing and distance from the remains of the original bearing trees:

- A Fir 42" dia., bears S.69°E., 142 lks. dist., with healed blaze.
- A decayed Fir stump, 60" dia., bears S.66°W., 79 lks. dist., no marks visible on decayed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

S 14	
S 22	S 23
T 24 S	R 7 W
C C	
1973	

from which a new bearing tree

- A Hemlock 17" dia., bears S.30°W., 67½ lks. dist. mkd. T24S R7W S22 CC BT.

Fd. Ok by C. Sweeden, 8/2005 - 2005-0084 A&B