

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 534600

PRIMARY CORNER DESCRIPTION M.C. between Secs. 2 & 11

Alias 868720 Description M.C. Left Bank Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73 dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3202)

-----  
Marked an Alder, 18" dia., for meander post, left bank, from which

A Myrtle, 18" dia., bears S.70°W., 43 lks.

A Myrtle, 12" dia., bears N.70°W., 57 lks.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19837)

-----  
Point selected for the witness cor. to the meander cor. of secs. 2 & 1, for the left bank of the Umpqua River.

Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T24S R7W

WC  
S 2 MC  
S 11  
1994

from which

A maple, 8" diam., bears N.25°E., 12 lks., mkd. X BT.

A maple, 22" diam., bears S.52°E., 38 lks., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located on level land West, 0.35 chs. dist. from top of the left bank of the Umpqua River, edge bears N.10°E. and S.10°W., and East, 0.05 chs. from a woven wire fence, extending N.35°W. & S.35°E.

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - 8/25/2014 - C.S. File 67/41-61

-----  
Found as described.

Found BTs are re-tagged and flagged.

Note - As previously described and also just north of a pasture in mixed river's edge woods composed of myrtle, maple, alder and fir.

Compass decl. 15½°E.