

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; & 2, T.25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3228)

Set a post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor., mkd. 1/4 S on N. face, from which
A Fir 24" dia., bears S.24°W., 12 lks. mkd. 1/4 S BT.
A Fir 16" dia., bears N.21°E., 63 lks., mkd. 1/4 S BT.

Bureau of Land Management resurvey by Lynn Roseberry, Group #645 Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Page 14950)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd:

T 24 S R 7 W
1/4 $\frac{S \ 35}{S \ 2}$
T 25 S
1967

from which

A Fir 10" dia., bears N.29 1/2°W., 51 1/2 lks., mkd. 1/4 S35 BT.
A Fir 8" dia., bears S.39 1/4°E., 78 lks., mkd. 1/4 S2 BT.

Found OK by D. Edwards, Nov. 2001 - M139-10

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21585-6)

The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Roseberry

A fir, 24" dia., bears S.39 1/4°E., 51.5 ft., with a healed blaze.

A fir, 23" dia., bears N.29 1/2°W., 34.0 ft., with a healed blaze.