

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3243)

-----  
A point about 700 ft. below section corner, Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Cedar 30" dia., bears N.55°W., 9 lks. dist. mkd. ¼ S BT  
A Fir 50" dia., bears S.74°E., 42 lks. dist. mkd. ¼ S BT

Survey by Les Roberts LS #1039 - For: International Paper Co. May 10, 1982 - M 92-36

-----  
Found - 36" Cedar bears N.55°W., 5.9 ft., scar visible.  
60" Fir bears S.74°E., 27.7 ft., bark scribed.  
Set 1½" x 36" I.P. with brass cap mkd. with sec., township and range, date and PLS #1039, from which new BTs:  
12" W.Fir bears N.77°E., 5.9 ft., scribed.  
14" W.Fir bears S.25°W., 10.8 ft., scribed.

Fd. OK, Feb. 18, 1992 by DCSO - C.S. File 64/24-9