

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3246-47)

Set a sandstone 14x12x10 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 40" dia., bears N.20°W., 11 lks. dist. mkd. ¼ S BT
A Fir 24" dia., bears S.46°E., 15 lks. dist. mkd. ¼ S BT

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15290)

The ¼ sec. cor., monumented with the original sandstone 14x12x10 ins., firmly set, 6" in the ground, mkd. ¼ on N. face, from which the original bearing trees:
A Fir 48" dia., bears N.16°W., 11 lks. dist. with healed blaze. (Rec. N.20°W.)
A Fir 36" dia., bears S.55°E., 15 lks. dist., with healed blaze. (Rec. S.46°E.)

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
¼ S 23
 S 26
 T 24 S R 7 W
 1973

Deposit corner stone alongside iron post.

Ronald Quimby - 2/2001 - C.S. File 65/36-4

Found - BLM brass cap & both BTs per BLM
New - A 12" D.Fir N.36°E., 39.2 ft., scribed ¼ S23 BT.
 A 12" Myrtle bears S.35°E., 32.0 ft. scribed ¼ S26 BT.