

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3200)

Set ¼ sec. post, from which
 A Laurel 6" dia., bears S.2°W., 6 lks. dist.
 A Laurel 9" dia., bears N.88°E., 25 lks. dist.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15291-92)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
 1/4 S 14
 T 24 S R 7 W
 1973

from which
 A Chinquapin 24" dia., bears N.56°E., 7½ lks. dist. mkd. ¼ S14 BT.
 A Fir 21" dia., bears N.73°W., 51½ lks. dist. mkd. ¼ S14 BT.

Fd. OK by C. Sweeden, July 1999 - M131-79
Fd. Ok by C. Sweeden, 8/2005 - 2005-0084 A&B