

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3251)

A Fir 12" dia., which I mark ¼ S on N. face, for ¼ sec. cor., from which
 A Fir 14" dia., bears N.40°W., 34 lks. dist. mkd. ¼ S BT.
 A W.Oak 5" dia., bears S.37°E., 15 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: N.E. Richardson; T.E. Higgenbottom; Buster Higgenbottom - Nov. 17, 1938 - C.S. File 37/201

Original corner tree 12" dia. now 18" dia. in place & in good shape. Orig. scar has been chopped out. Scribe mks. vis. Drove a 1" x 18" pipe along side original cor. tree. Remark the orig. corner tree in the bark "¼S 11 on N. face, and ¼S 14 CS on S. face, from which
 Orig. BT, Fir 14" dia., now 30" dia., N.40°W., 34 lks., alive & in fair shape. Orig. scar has been chopped out and scribe marks are barely legible. I scribe "¼S 11 CS BT" in BT, in bark.
New BTs:
 Fir 20" dia., S.15°E., 42 ft. scribed ¼ S14 CS BT.
 Fir 20" dia., N.62°W., 16 ft. scribed ¼ S11 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 30, 1958 - C.S. File 49/41-15

Fd all BTs & pipe as recorded by Irving, except SE. BT, which is now stump only. Also, scribed corner BT is now down. Set brass cap at corner and alongside 1" I.P., mkd. "¼ S11 S14 T24S R7W County Surveyors Office 1958".
New BT - 11" W.Fir bears S.23°W. 62.5 ft. scribed ¼ S14 CS BT

Fd. OK, May 1985 by L. Dolan - M 98-65

Carl Sweeden - For: Avis Ocumpaugh - July 1999 - M 131-79

Found - Brass cap
 30" W.Fir, S.23°W., 62.5 ft. tagged.
 20" D.Fir, N.62°W., 16.0 ft. not found.
 33" D.Fir, N.40°W., 22.4 ft. tagged tree is dead.
 20" D.Fir S.15°E., 42.0 ft. not found.
BTs not of rec.
 14" D.Fir, N.52°W., 18.4 ft. tagged, scar visible.
 21" D.Fir, N.62°W., 10.4 ft. tagged, tree is dead.

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19833)

The ¼ sec. cor. of secs. 11 & 14, perpetuated by Irving, Deputy County Surveyor, in 1938, further perpetuated by Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1¼" diam., firmly set, projecting 16" above ground, with properly marked brass cap, from which the remains of an original bearing tree

- A fir snag, 30" diam., bears N.40°W., 34 lks., with healed blaze.
- and the remains of bearing trees mkd. by Irving
 - A fir stump, 23" diam., bears S.10°E., 42 lks., with scribe marks BT visible on bark blaze.
 - A fir snag, 20" diam., bears N.62°W., 16 lks., with healed double blaze.
- and a bearing tree mkd. by Byron
 - A hemlock, 28" diam., bears S.23°W., 95 lks., with healed blaze.
- and a new bearing tree
 - A fir, 12" diam., bears N.74°W., 28 lks., mkd. ¼ S11 BT.

The corner is located on a SW. slope on S. edge of timber, edge bears E. & W.

Fd. Ok by C. Sweeden, 8/2005 - 2005-0084 A&B

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22373)

The ¼ sec. cor. of secs. 8 and 17, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by the Douglas County Surveyors Office in 1963, reported by Jelley

- A fir, 17" dia., bears S.40¾°E., 17.5 ft., with a healed blaze. (Record, S.43°E.)
- A decayed fir snag, 19" dia., bears N.44¾°W., 35.4 ft., with a healed blaze. (Record, 36.3 ft.)

and new bearing tree

- A fir, 11" dia., bears N.30¾°W., 29.3 ft., mkd. ¼ S8 BT.