

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 540540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19839)

Point for the center ¼ sec. cor. of sec. 11, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T24S R7W
C ¼ S 11
1994

from which

A fir, 13" diam., bears S.56¼°E., 4 lks., mkd. C ¼ S11 BT.

A fir, 35" diam., bears S.74½°W., 10 lks., mkd. C¼ S11 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located on a steep NE. slope, 0.50 chs. dist., NE. of a rock bluff, 15 ft. high.

Fd. & used on BLM Dependent resurvey by Wayne Rogers & A. Bert Skeesick, Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1878, surveyed May 1998 - Jan. 2000 - (DCSO records Vol. 53 Page(s) 20440-1)